

Heisener.com

## CA06COMPG20-15PB

#### **CA06COMPG20-15PB Information**

Part Number CA06COMPG20-15PB
Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 7POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA06COMPG20-15PB Specifications**

Manufacturer Part NumberCA06COMPG20-15PBManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesSealing GlandVoltage - Rated500VAC, 700VDCCurrent Rating41A		
Category Circular Connectors Circular Connectors  Package - Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 20-15 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Sealing Gland Voltage - Rated So0VAC, 700VDC	Manufacturer Part Number	CA06COMPG20-15PB
Circular Connectors  Package Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 20-15 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Sealing Gland Voltage - Rated  Convertified  Connector Sullar Connectors MIL-DTL-5015, CA-COM-B	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 20-15 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 20-15 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC		Circular Connectors
Connector Type Plug, Male Pins  Number of Positions 7  Shell Size - Insert 20-15  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features Sealing Gland  Voltage - Rated 500VAC, 700VDC	Package	-
Number of Positions  Shell Size - Insert  20-15  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Sealing Gland  Voltage - Rated  500VAC, 700VDC	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Sealing Gland  Voltage - Rated  20-15  Aluminum Silver  Sealing Gland  500VAC, 700VDC	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Number of Positions	7
Mounting Type Free Hanging (In-Line)  Solder Cup  Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated  Free Hanging (In-Line)  Reverse Bayonet Lock N (Normal)  IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver Features Sealing Gland	Shell Size - Insert	20-15
Termination Solder Cup  Fastening Type Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver  Features Sealing Gland  Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Sealing Gland  Voltage - Rated  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  Sealing Gland	Orientation	N (Normal)
Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	Sealing Gland
Current Rating 41A	Voltage - Rated	500VAC, 700VDC
	Current Rating	41A
Report errors?		Report errors?

### **CA06COMPG20-15PB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CA06COMPG20-15PB Payment Methods**



















## **CA06COMPG20-15PB Shipping Methods**













If you have any question about CA06COMPG20-15PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com