



CA06COMPG22-22S Information

Heisener.com

Part Number CA06COMPG22-22S Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 4POS INLINE W/SKTS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA06COMPG22-22S Specifications

Manufacturer Part NumberCA06COMPG22-22SManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COMConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert22-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesSealing GlandVoltage - Rated500VAC, 700VDC		
Category Circular Connectors Circular Connectors Package - Series MIL-DTL-5015, CA-COM Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated SoovAC, 700VDC	Manufacturer Part Number	CA06COMPG22-22S
Circular Connectors Package Series MIL-DTL-5015, CA-COM Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Sealing Gland Voltage - Rated Convertified Type Siver Features Sealing Gland Voltage - Rated	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Package	-
Number of Positions Shell Size - Insert 22-22 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Series	MIL-DTL-5015, CA-COM
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Number of Positions	4
Mounting Type Free Hanging (In-Line) Solder Cup Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated Free Hanging (In-Line) Solder Cup Threaded N (Normal) IP65 - Dust Tight, Water Resistant Shell Material, Finish Silver Features Solder Cup Threaded Silver Resistant Shell Material, Finish Silver Features Solder Cup Threaded Solder Cup Threaded Solder Cup Solder Cup Threaded Solder	Shell Size - Insert	22-22
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Sealing Gland Voltage - Rated Aluminum Alloy, Zinc Die Cast, Nickel Plated Silver Sealing Gland	Orientation	N (Normal)
Contact Finish Silver Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Sealing Gland Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	Sealing Gland
	Voltage - Rated	500VAC, 700VDC
Current Rating 74A	Current Rating	74A
Report errors?		Report errors?

CA06COMPG22-22S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA06COMPG22-22S Payment Methods



















CA06COMPG22-22S Shipping Methods













If you have any question about CA06COMPG22-22S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com