



CA06R18-12PZF80 Information

Heisener.com

Part Number CA06R18-12PZF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 6POS INLINE W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA06R18-12PZF80 Specifications

Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 18-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver		
Category Circular Connectors Package Package Package Plug, Male Pins Number of Positions Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation Z Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Voltage - Rated Voltage - Rated Voltage - Rated Circular Connectors MIL-DTL-5015, CA Plug, Male Pins Allumicuts Finish Connectors	Manufacturer Part Number	CA06R18-12PZF80
Circular Connectors Package Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 18-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation Z Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Circular Connectors MIL-DTL-5015, CA MIL-DTL-5015, CA Plug, Male Pins Plug, Male Pins Plug, Male Pins NIL-DTL-5015, CA Plug, Male Pins Plug, Male Pins Plug, Male Pins Pree Hanging (In-Line) Crimp Free Hanging (In-Line) Trimp Free Hanging (In-Line) Crimp Free Hanging (In-Line) Crimp Free Hanging (In-Line) Crimp Free Hanging (In-Line) Crimp Free Hanging (In-Line) Free Hanging (In-Line) Crimp Free Hanging (In-Li	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 18-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 18-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert18-12Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationZIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Package	-
Number of Positions Shell Size - Insert 18-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation Z Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 6 18-12 18-12 5 18-12 5 18-12 5 18-12 5 Free Hanging (In-Line) Crimp Threaded Crimp Threaded Crimp Threaded Aluminum Alloy Colve Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 18-12 18-	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated	Number of Positions	6
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Shell Size - Insert	18-12
Termination Crimp Fastening Type Threaded Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Shell Size, MIL	-
Fastening Type Threaded Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Threaded Z Threaded Z Threaded S Substitute S Silver Silver Strain Relief	Mounting Type	Free Hanging (In-Line)
Orientation Z Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Termination	Crimp
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Fastening Type	Threaded
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Orientation	Z
Contact Finish Silver Features Strain Relief Voltage - Rated 50V	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief Voltage - Rated 50V	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V	Contact Finish	Silver
	Features	Strain Relief
Current Rating 22A	Voltage - Rated	50V
	Current Rating	22A
Report errors?		Report errors?

CA06R18-12PZF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA06R18-12PZF80 Payment Methods



















CA06R18-12PZF80 Shipping Methods













If you have any question about CA06R18-12PZF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com