



## CA06R20-29SA176 Information

Heisener.com

Part Number CA06R20-29SA176 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 17POS INLINE W/SKTS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA06R20-29SA176 Specifications

Manufacturer Part Number     CA06R20-29SA176       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CA       Connector Type     Plug, Female Sockets       Number of Positions     17       Shell Size - Insert     20-29       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     IP65 - Dust Tight, Water Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     Strain Relief       Voltage - Rated     50V       Current Rating     22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA06R20-29SA176
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief  Voltage - Rated 50V Current Rating 22A	Number of Positions	17
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Size - Insert	20-29
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Gold  Strain Relief  22A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief  Voltage - Rated 50V  Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Gold
Current Rating 22A	Features	Strain Relief
-	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

### CA06R20-29SA176 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CA06R20-29SA176 Payment Methods



















## CA06R20-29SA176 Shipping Methods













If you have any question about CA06R20-29SA176, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com