

## CA06R28-2PF80 Information

Heisener.com

**Part Number** CA06R28-2PF80 **Manufacturer** ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 14POS INLINE W/PINS

Package -


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CA06R28-2PF80 Specifications**

Manufacturer Part Number       CA06R28-2PF80         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA         Connector Type       Plug, Male Pins         Number of Positions       14         Shell Size - Insert       28-2         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       IP65 - Dust Tight, Water Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       50V         Current Rating       22A, 41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions14Shell Size - Insert28-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A	Manufacturer Part Number	CA06R28-2PF80
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions14Shell Size - Insert28-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions14Shell Size - Insert28-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA  Connector Type Plug, Male Pins  Number of Positions 14  Shell Size - Insert 28-2  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection IP65 - Dust Tight, Water Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 50V  Current Rating 22A, 41A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions14Shell Size - Insert28-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A	Package	-
Number of Positions  Shell Size - Insert  28-2  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  14  28-2  28-2  Strain Relief  Free Hanging (In-Line)  Crimp  Free Hanging (In-Line)  Aluminum Alloy  Crimp  Stree Hanging (In-Line)  Crimp  Free Hanging (In-Line)  Crimp  Aluminum Alloy  Strain Resistant  Aluminum Alloy  Silver  Strain Relief  Voltage - Rated  Sov  Current Rating  22A, 41A	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A, 41A	Number of Positions	14
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A	Shell Size - Insert	28-2
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A, 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Termination	Crimp
Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A, 41A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Strain Relief  22A, 41A	Orientation	N (Normal)
Contact Finish Silver  Features Strain Relief Voltage - Rated Current Rating 22A, 41A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief  Voltage - Rated 50V  Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	Strain Relief
	Voltage - Rated	50V
Report errors?	Current Rating	22A, 41A
I .		Report errors?

#### CA06R28-2PF80 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA06R28-2PF80 Payment Methods



















### **CA06R28-2PF80 Shipping Methods**













If you have any question about CA06R28-2PF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com