

CA1041 Information

1

Heisener.com

For Reference Only

Part Number CA1041 Manufacturer Ohmite

Category Potentiometers, Variable Resistors

Rotary Potentiometers, Rheostats

Description POT 100K OHM 2W CARBON LOG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA1041 Specifications

Manufacturer Part Number CA1041 Manufacturer Ohmite Category Potentiometers, Variable Resistors Package - Series CA Taper Logarithmic Resistance (Ohms) 100k Number of Gangs 1 Built in Switch None Power (Watts) 2W Temperature Coefficient - Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	*	
Category Potentiometers, Variable Resistors Package - Series CA Taper Logarithmic Resistance (Ohms) 100k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 2W Temperature Coefficient - Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Manufacturer Part Number	CA1041
Package - Series CA Taper Logarithmic Resistance (Ohms) 100k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 2W Temperature Coefficient - Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Manufacturer	Ohmite
Package - Series CA Taper Logarithmic Resistance (Ohms) 100k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 2W Temperature Coefficient - Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Category	Potentiometers, Variable Resistors
Series CA Taper Logarithmic Resistance (Ohms) 100k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 2W Temperature Coefficient - Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount		Rotary Potentiometers, Rheostats
Taper Logarithmic Resistance (Ohms) 100k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 2W Temperature Coefficient - Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Package	-
Resistance (Ohms) 100k Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 2W Temperature Coefficient - Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Series	CA
Tolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)2WTemperature Coefficient-Number of Turns1Rotation312°Adjustment TypeUser DefinedResistive MaterialCarbonTermination StyleSolder LugActuator TypeRoundActuator Length2.000" (50.80mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Taper	Logarithmic
Number of Gangs1Built in SwitchNonePower (Watts)2WTemperature Coefficient-Number of Turns1Rotation312°Adjustment TypeUser DefinedResistive MaterialCarbonTermination StyleSolder LugActuator TypeRoundActuator Length2.000" (50.80mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Resistance (Ohms)	100k
Built in SwitchNonePower (Watts)2WTemperature Coefficient-Number of Turns1Rotation312°Adjustment TypeUser DefinedResistive MaterialCarbonTermination StyleSolder LugActuator TypeRoundActuator Length2.000" (50.80mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Tolerance	±10%
Power (Watts) Temperature Coefficient - Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length Actuator Diameter 0.250" (6.35mm) Bushing Thread Mounting Type Panel Mount	Number of Gangs	1
Temperature Coefficient Number of Turns 1 Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length Actuator Diameter 0.250" (50.80mm) Bushing Thread Mounting Type Panel Mount	Built in Switch	None
Number of Turns Rotation 312° Adjustment Type User Defined Carbon Termination Style Actuator Type Round Actuator Length Actuator Diameter Bushing Thread Mounting Type 1 1 1 1 1 1 1 1 1 1 1 1 1	Power (Watts)	2W
Rotation 312° Adjustment Type User Defined Resistive Material Carbon Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Temperature Coefficient	-
Adjustment Type Resistive Material Carbon Termination Style Actuator Type Round Actuator Length Actuator Diameter Bushing Thread Mounting Type User Defined Carbon Carbon Solder Lug Round 2.000" (50.80mm) 0.250" (6.35mm) Panel Mount	Number of Turns	1
Resistive MaterialCarbonTermination StyleSolder LugActuator TypeRoundActuator Length2.000" (50.80mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Rotation	312°
Termination Style Solder Lug Actuator Type Round Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Adjustment Type	User Defined
Actuator TypeRoundActuator Length2.000" (50.80mm)Actuator Diameter0.250" (6.35mm)Bushing Thread3/8-32Mounting TypePanel Mount	Resistive Material	Carbon
Actuator Length 2.000" (50.80mm) Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Termination Style	Solder Lug
Actuator Diameter 0.250" (6.35mm) Bushing Thread 3/8-32 Mounting Type Panel Mount	Actuator Type	Round
Bushing Thread 3/8-32 Mounting Type Panel Mount	Actuator Length	2.000" (50.80mm)
Mounting Type Panel Mount	Actuator Diameter	0.250" (6.35mm)
	Bushing Thread	3/8-32
Report errors?	Mounting Type	Panel Mount
		Report errors?

CA1041 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA1041 Payment Methods



















CA1041 Shipping Methods













If you have any question about CA1041, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com