



CA20COME22-14PB Information

Heisener.com

Part Number CA20COME22-14PB Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 19POS BOX MNT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA20COME22-14PB Specifications

Manufacturer Part Number CA20COME22-14PB Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 22-14 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer Part Number	CA20COME22-14PB
Circular Connectors Package - Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 22-14 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features - Voltage - Rated Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 22-14 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 22-14 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Package	-
Number of Positions Shell Size - Insert 22-14 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating 19 22-14 22-14 22-14 2-14 2	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Number of Positions	19
Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Size - Insert	22-14
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Zinc Die Cast, Nickel Plated Silver - Voltage - Rated 500VAC, 700VDC 22A	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating Silver - 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A
		Report errors?

CA20COME22-14PB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA20COME22-14PB Payment Methods





















CA20COME22-14PB Shipping Methods













If you have any question about CA20COME22-14PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com