

Heisener.com

# **CA20COME24-10PB01**

## CA20COME24-10PB01 Information

Part Number CA20COME24-10PB01
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 7POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CA20COME24-10PB01 Specifications**

Manufacturer Part Number     CA20COME24-10PB01       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CA-COM-B       Connector Type     Receptacle, Male Pins       Number of Positions     7       Shell Size - Insert     24-10       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Reverse Bayonet Lock       Orientation     N (Normal)       Ingress Protection     IP67 - Dust Tight, Waterproof       Shell Material, Finish     Aluminum Alloy, Zinc Die Cast, Nickel Plated       Contact Finish     Silver       Features     -       Voltage - Rated     500VAC, 700VDC       Current Rating     74A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating74A	Manufacturer Part Number	CA20COME24-10PB01
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating74A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating74A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating74A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating74A	Package	-
Number of Positions  Shell Size - Insert  24-10  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Features  Voltage - Rated  500VAC, 700VDC  Current Rating  74A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 74A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating 74A	Number of Positions	7
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating 74A	Shell Size - Insert	24-10
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 74A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 74A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 74A	Termination	Crimp
Ingress Protection  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  - Voltage - Rated  500VAC, 700VDC  Current Rating	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  -  Voltage - Rated  500VAC, 700VDC  74A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating 74A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating 74A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC Current Rating 74A	Contact Finish	Silver
Current Rating 74A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	74A
		Report errors?

#### CA20COME24-10PB01 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA20COME24-10PB01 Payment Methods





















### **CA20COME24-10PB01 Shipping Methods**













If you have any question about CA20COME24-10PB01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com