



## CA20COML14S-5SB Information

Heisener.com

Part Number CA20COML14S-5SB Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

CONN RCPT 5POS BOX MNT W/SKTS **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA20COML14S-5SB Specifications**

Manufacturer Part Number       CA20COML14S-5SB         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA-COM-B         Connector Type       Receptacle, Female Sockets         Number of Positions       5         Shell Size - Insert       14S-5         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange; Through Hole         Termination       Solder         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Zinc Die Cast, Nickel Plated         Contact Finish       Silver         Features       -         Voltage - Rated       200VAC, 250VDC         Current Rating       22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A	Manufacturer Part Number	CA20COML14S-5SB
Circular Connectors  Package - Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 14S-5 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 14S-5 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Woltage - Rated 200VAC, 250VDC Current Rating 22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 14S-5 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A	Package	-
Number of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange; Through Hole  Termination  Solder  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  -  Voltage - Rated  200VAC, 250VDC  Current Rating  22A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange; Through Hole  Termination Solder  Raverse Bayonet Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Number of Positions	5
Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Size - Insert	14S-5
Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Mounting Type	Panel Mount, Flange; Through Hole
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Termination	Solder
Ingress Protection  Shell Material, Finish  Contact Finish  Features  Voltage - Rated  Current Rating  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  -  200VAC, 250VDC  22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  - 200VAC, 250VDC  22A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating 200VAC, 250VDC 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 200VAC, 250VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
-	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	22A
		Report errors?

### CA20COML14S-5SB Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CA20COML14S-5SB Payment Methods**





















## CA20COML14S-5SB Shipping Methods













If you have any question about CA20COML14S-5SB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com