



CA3100E20A48SB08 Information

Heisener.com

Part NumberCA3100E20A48SB08ManufacturerITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 19POS WALL MNT W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3100E20A48SB08 Specifications

Manufacturer Part Number Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 20-A48 Shell Size, MIL Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 50V Current Rating 22A Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 20-A48 Shell Size, MIL - Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Manufacturer Part Number	CA3100E20A48SB08
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 20-A48 Shell Size, MIL - Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 50V Current Rating 2 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 20-A48 Shell Size, MIL - Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 20-A48 Shell Size, MIL - Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 20-A48 Shell Size, MIL Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Package	-
Number of Positions Shell Size - Insert 20-A48 Shell Size, MIL Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 50V Current Rating 22A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 50V Current Rating 22A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Number of Positions	19
Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size - Insert	20-A48
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Mounting Type	Panel Mount, Flange, Right Angle
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Strain Relief 22A	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Strain Relief
-	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3100E20A48SB08 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3100E20A48SB08 Payment Methods



















CA3100E20A48SB08 Shipping Methods













If you have any question about CA3100E20A48SB08, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com