



### CA3100E24-11PF80 Information

Heisener.com

**Part Number** CA3100E24-11PF80 **Manufacturer** ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 9POS WALL MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CA3100E24-11PF80 Specifications

| Manufacturer Part Number       CA3100E24-11PF80         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA         Connector Type       Receptacle, Male Pins         Number of Positions       9         Shell Size - Insert       24-11         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       IP65 - Dust Tight, Water Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       50V         Current Rating       41A, 74A         Report errors? |                          |   |
|--|--------------------------|---|
| Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 9 Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 41A, 74A  | Manufacturer Part Number | CA3100E24-11PF80                          |
| Circular Connectors  Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 9 Shell Size - Insert 24-11 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 50V Current Rating 41A, 74A  | Manufacturer             | ITT Cannon, LLC                           |
| Package - MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 9 Shell Size - Insert 24-11 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 41A, 74A   | Category                 | Connectors, Interconnects                 |
| Series MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 9 Shell Size - Insert 24-11 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A, 74A  |                          | Circular Connectors                       |
| Connector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert24-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A, 74A   | Package                  | -   |
| Number of Positions  Shell Size - Insert  24-11  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  50V  Current Rating  41A, 74A  | Series                   | MIL-DTL-5015, CA                          |
| Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  50V  Current Rating  41A, 74A  | Connector Type           | Receptacle, Male Pins                     |
| Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A, 74A  | Number of Positions      | 9   |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A, 74A  | Shell Size - Insert      | 24-11                                     |
| Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A, 74A   | Shell Size, MIL          | -   |
| Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  50V  Current Rating  41A, 74A  | Mounting Type            | Panel Mount, Flange                       |
| Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A, 74A   | Termination              | Crimp                                     |
| Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  41A, 74A  | Fastening Type           | Threaded                                  |
| Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Strain Relief  41A, 74A   | Orientation              | N (Normal)                                |
| Contact Finish Silver  Features Strain Relief Voltage - Rated Current Rating 41A, 74A  | Ingress Protection       | IP65 - Dust Tight, Water Resistant        |
| Features Strain Relief  Voltage - Rated 50V  Current Rating 41A, 74A   | Shell Material, Finish   | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 50V<br>Current Rating 41A, 74A   | Contact Finish           | Silver                                    |
| Current Rating 41A, 74A  | Features                 | Strain Relief                             |
| -  | Voltage - Rated          | 50V                                       |
| Report errors?   | Current Rating           | 41A, 74A                                  |
|  |                          | Report errors?                            |

#### CA3100E24-11PF80 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CA3100E24-11PF80 Payment Methods



















# CA3100E24-11PF80 Shipping Methods













If you have any question about CA3100E24-11PF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com