



## CA3100E24-12PB15 Information

Heisener.com

**Part Number** CA3100E24-12PB15 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 5POS WALL MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3100E24-12PB15 Specifications

Manufacturer Part Number       CA3100E24-12PB15         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA-B         Connector Type       Receptacle, Male Pins         Number of Positions       5         Shell Size - Insert       24-12         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Shielded         Voltage - Rated       50V         Current Rating       41A, 135A         Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Current Rating 41A, 135A	Manufacturer Part Number	CA3100E24-12PB15
Circular Connectors  Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated 50V Current Rating 41A, 135A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 41A, 135A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 41A, 135A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert24-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating41A, 135A	Package	-
Number of Positions  Shell Size - Insert  24-12  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Shielded  Voltage - Rated  50V  Current Rating  41A, 135A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Shielded  Voltage - Rated  50V  Current Rating  41A, 135A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 41A, 135A	Number of Positions	5
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating41A, 135A	Shell Size - Insert	24-12
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 41A, 135A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 41A, 135A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 41A, 135A	Termination	Crimp
Ingress Protection  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Shielded  Voltage - Rated  Current Rating  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Shielded  41A, 135A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Shielded  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Shielded  41A, 135A	Orientation	N (Normal)
Contact Finish Silver  Features Shielded Voltage - Rated Current Rating 41A, 135A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shielded  Voltage - Rated 50V  Current Rating 41A, 135A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 41A, 135A	Contact Finish	Silver
Current Rating 41A, 135A	Features	Shielded
-	Voltage - Rated	50V
Report errors?	Current Rating	41A, 135A
		Report errors?

### CA3100E24-12PB15 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CA3100E24-12PB15 Payment Methods



















## CA3100E24-12PB15 Shipping Methods













If you have any question about CA3100E24-12PB15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com