



CA3100E28-22PB03 Information

Heisener.com

Part Number CA3100E28-22PB03 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 6POS WALL MNT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3100E28-22PB03 Specifications

Manufacturer Part NumberCA3100E28-22PB03ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50V		
Category Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Voltage - Rated Connectors, Interconnects Circular Connectors - Connector Type Receptacle, Male Pins - Connector Type Receptacle - Connector Type Rec	Manufacturer Part Number	CA3100E28-22PB03
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50V	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V	Package	-
Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shrink Boot Adapter Voltage - Rated 50V	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V	Number of Positions	6
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50V	Shell Size - Insert	28-22
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated Aluminum Alloy, Olive Drab Cadmium Plated Silver Solver Shrink Boot Adapter	Orientation	N (Normal)
Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shrink Boot Adapter Voltage - Rated 50V	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V	Contact Finish	Silver
	Features	Shrink Boot Adapter
	Voltage - Rated	50V
Current Rating 22A, 135A	Current Rating	22A, 135A
Report errors?		Report errors?

CA3100E28-22PB03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3100E28-22PB03 Payment Methods



















CA3100E28-22PB03 Shipping Methods













If you have any question about CA3100E28-22PB03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com