

Heisener.com

CA3100E36-10PB02-05A176

CA3100E36-10PB02-05A176 Information

Part Number CA3100E36-10PB02-05A176

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 48POS WALL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3100E36-10PB02-05A176 Specifications

Manufacturer Part NumberCA3100E36-10PB02-05A176ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3100E36-10PB02-05A176
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 48 Shell Size - Insert 36-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Number of Positions	48
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Shell Size - Insert	36-10
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Gold Contact Finish Gold Shrink Boot Adapter 22A	Orientation	N (Normal)
Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Gold
Current Rating 22A	Features	Shrink Boot Adapter
	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3100E36-10PB02-05A176 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3100E36-10PB02-05A176 Payment Methods





















CA3100E36-10PB02-05A176 Shipping Methods













If you have any question about CA3100E36-10PB02-05A176, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com