



CA3100ER14S-7S Information

Heisener.com

Part Number CA3100ER14S-7S Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 3POS WALL MNT W/SKTS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3100ER14S-7S Specifications

Manufacturer Part Number CA3100ER14S-7S Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 14S-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 14S-7 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating 22A	Manufacturer Part Number	CA3100ER14S-7S
Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 14S-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 14S-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 14S-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert14S-7Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Package	-
Number of Positions Shell Size - Insert 14S-7 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 50V Current Rating 22A	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 14S-7 Panel Mount, Flange Panel Mount, Flange Panel Mount, Flange Panel Mount, Flange Solder Cup Threaded Aluminum Alloy Solder Cup Threaded N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Number of Positions	3
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Shell Size - Insert	14S-7
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 50V Current Rating Threaded N (Normal) IP65 - Dust Tight, Water Resistant Aluminum Plated Silver - 22A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Silver - 22A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 22A	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3100ER14S-7S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3100ER14S-7S Payment Methods



















CA3100ER14S-7S Shipping Methods













If you have any question about CA3100ER14S-7S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com