



### CA3100F18-10S Information

Heisener.com

**Part Number** CA3100F18-10S **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 4POS WALL MNT W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CA3100F18-10S Specifications**

Manufacturer Part Number     CA3100F18-10S       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CA       Connector Type     Receptacle, Female Sockets       Number of Positions     4       Shell Size - Insert     18-10       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     IP65 - Dust Tight, Water Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     50V       Current Rating     41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Manufacturer Part Number	CA3100F18-10S
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Package	-
Number of Positions4Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Series	MIL-DTL-5015, CA
Shell Size - Insert18-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 50V  Current Rating 41A	Number of Positions	4
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Shell Size - Insert	18-10
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 41A	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V Current Rating 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 41A	Contact Finish	Silver
Current Rating 41A	Features	-
	Voltage - Rated	50V
Report errors?	Current Rating	41A
		Report errors?

#### CA3100F18-10S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# CA3100F18-10S Payment Methods



















### **CA3100F18-10S Shipping Methods**













If you have any question about CA3100F18-10S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com