



## CA3100F24-7SB08 Information

Heisener.com

Part Number CA3100F24-7SB08 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 16POS WALL MNT W/SKTS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3100F24-7SB08 Specifications

| Manufacturer Part Number     CA3100F24-78B08       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     MIL-DTL-5015, CA-B       Connector Type     Receptacle, Female Sockets       Number of Positions     16       Shell Size - Insert     24-7       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange, Right Angle       Termination     Solder Cup       Fastening Type     Reverse Bayonet Lock       Orientation     N (Normal)       Ingress Protection     IP67 - Dust Tight, Waterproof       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     50V       Current Rating     22A, 41A |                          |   |
|--|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - Insert24-7Shell Size, MIL-Mounting TypePanel Mount, Flange, Right AngleTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A  | Manufacturer Part Number | CA3100F24-7SB08                           |
| Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - Insert24-7Shell Size, MIL-Mounting TypePanel Mount, Flange, Right AngleTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A   | Manufacturer             | ITT Cannon, LLC                           |
| Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 16 Shell Size - Insert 24-7 Shell Size, MIL - Mounting Type Panel Mount, Flange, Right Angle Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 22A, 41A   | Category                 | Connectors, Interconnects                 |
| Series MIL-DTL-5015, CA-B  Connector Type Receptacle, Female Sockets  Number of Positions 16  Shell Size - Insert 24-7  Shell Size, MIL  |                          | Circular Connectors                       |
| Connector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - Insert24-7Shell Size, MIL-Mounting TypePanel Mount, Flange, Right AngleTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A   | Package                  | -   |
| Number of Positions  Shell Size - Insert  24-7  Shell Size, MIL  Mounting Type  Panel Mount, Flange, Right Angle  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  50V  Current Rating  22A, 41A  | Series                   | MIL-DTL-5015, CA-B                        |
| Shell Size - Insert Shell Size, MIL  | Connector Type           | Receptacle, Female Sockets                |
| Shell Size, MIL  Mounting Type Panel Mount, Flange, Right Angle  Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A, 41A   | Number of Positions      | 16  |
| Mounting TypePanel Mount, Flange, Right AngleTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A   | Shell Size - Insert      | 24-7                                      |
| Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A   | Shell Size, MIL          | -   |
| Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A  | Mounting Type            | Panel Mount, Flange, Right Angle          |
| Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A  | Termination              | Solder Cup                                |
| Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A   | Fastening Type           | Reverse Bayonet Lock                      |
| Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver   | Orientation              | N (Normal)                                |
| Contact Finish  Features  Voltage - Rated  Current Rating  Silver  - 22A, 41A  | Ingress Protection       | IP67 - Dust Tight, Waterproof             |
| Features - Voltage - Rated 50V Current Rating 22A, 41A   | Shell Material, Finish   | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 50V<br>Current Rating 22A, 41A   | Contact Finish           | Silver                                    |
| Current Rating 22A, 41A  | Features                 | -   |
| -  | Voltage - Rated          | 50V                                       |
| Report errors?   | Current Rating           | 22A, 41A                                  |
|  |                          | Report errors?                            |

### CA3100F24-7SB08 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3100F24-7SB08 Payment Methods



















## CA3100F24-7SB08 Shipping Methods













If you have any question about CA3100F24-7SB08, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com