

Heisener.com

CA3100R18-8PF80A95

CA3100R18-8PF80A95 Information

Part Number CA3100R18-8PF80A95

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS WALL MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3100R18-8PF80A95 Specifications

Manufacturer Part NumberCA3100R18-8PF80A95ManufacturerITT Cannon, LLCCategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated50VCurrent Rating22A, 41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Manufacturer Part Number	CA3100R18-8PF80A95
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated50VCurrent Rating22A, 41A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Package	-
Number of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 50V Current Rating 18-8 Panel Mount, Flange Panel Mount, Flange Panel Mount, Flange Aluminum Plange String Type Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Current Rating 22A, 41A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 50V Current Rating 22A, 41A	Number of Positions	8
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Shell Size - Insert	18-8
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 50V Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 50V Current Rating 22A, 41A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 50V Current Rating 22A, 41A	Termination	Crimp
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Current Rating IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Gold Current Rating - 22A, 41A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Gold Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Gold Current Rating	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 50V Current Rating 22A, 41A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 41A	Contact Finish	Gold
Current Rating 22A, 41A	Features	-
	Voltage - Rated	50V
Report errors?	Current Rating	22A, 41A
		Report errors?

CA3100R18-8PF80A95 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3100R18-8PF80A95 Payment Methods



















CA3100R18-8PF80A95 Shipping Methods













If you have any question about CA3100R18-8PF80A95, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com