



### CA3100R24-10PB Information

Heisener.com

Part Number CA3100R24-10PB
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 7POS WALL MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **CA3100R24-10PB Specifications**

Manufacturer Part NumberCA3100R24-10PBManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A	Manufacturer Part Number	CA3100R24-10PB
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A	Package	-
Number of Positions7Shell Size - Insert24-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert 24-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 74A	Number of Positions	7
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A	Shell Size - Insert	24-10
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  74A	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating 74A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 74A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 74A	Contact Finish	Silver
Current Rating 74A	Features	-
	Voltage - Rated	50V
Report errors?	Current Rating	74A
		Report errors?

#### CA3100R24-10PB Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# CA3100R24-10PB Payment Methods



















### CA3100R24-10PB Shipping Methods













If you have any question about CA3100R24-10PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com