



Heisener.com

CA3101E20-27PWF80 Information

Part Number CA3101E20-27PWF80
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 14POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3101E20-27PWF80 Specifications

| Manufacturer Part Number CA3101E20-27PWF80 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 14 Shell Size - Insert 20-27 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A | | |
|--|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V | Manufacturer Part Number | CA3101E20-27PWF80 |
| Circular Connectors Package Series MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 14 Shell Size - Insert 20-27 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection W Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Columnt Circular Connectors MIL-DTL-5015, CA Receptacle, Male Pins I4 Shell Malerial, Finish Lauminum Alloy, Olive Drab Cadmium Plated Strain Relief Voltage - Rated | Manufacturer | ITT Cannon, LLC |
| Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V | Category | Connectors, Interconnects |
| SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V | | Circular Connectors |
| Connector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V | Package | - |
| Number of Positions Shell Size - Insert 20-27 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation W Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated | Series | MIL-DTL-5015, CA |
| Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 20-27 Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Aluminum Plated Silver Strain Relief | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V | Number of Positions | 14 |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V | Shell Size - Insert | 20-27 |
| Termination Crimp Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V | Shell Size, MIL | - |
| Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V | Mounting Type | Free Hanging (In-Line) |
| Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V | Termination | Crimp |
| Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Aluminum Alloy, Olive Drab Cadmium Plated Silver Strain Relief | Orientation | W |
| Contact Finish Silver Features Strain Relief Voltage - Rated 50V | Ingress Protection | IP65 - Dust Tight, Water Resistant |
| Features Strain Relief Voltage - Rated 50V | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 50V | Contact Finish | Silver |
| | Features | Strain Relief |
| Current Rating 22A | Voltage - Rated | 50V |
| č | Current Rating | 22A |
| Report errors? | | Report errors? |

CA3101E20-27PWF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3101E20-27PWF80 Payment Methods

































If you have any question about CA3101E20-27PWF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com