

Heisener.com

## CA3101E20-29PF80DN

## CA3101E20-29PF80DN Information

Part Number CA3101E20-29PF80DN

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 17POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CA3101E20-29PF80DN Specifications

Manufacturer Part Number     CA3101E20-29PF80DN       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CA       Connector Type     Receptacle, Male Pins       Number of Positions     17       Shell Size - Insert     20-29       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     IP65 - Dust Tight, Water Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     Shrink Boot Adapter       Voltage - Rated     50V       Current Rating     22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3101E20-29PF80DN
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA
Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shrink Boot Adapter  Voltage - Rated 50V Current Rating 22A	Number of Positions	17
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A	Shell Size - Insert	20-29
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Shrink Boot Adapter  Voltage - Rated  Current Rating  22A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Shrink Boot Adapter  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Shrink Boot Adapter  22A	Orientation	N (Normal)
Contact Finish Silver Shrink Boot Adapter Voltage - Rated Current Rating 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Shrink Boot Adapter  Voltage - Rated 50V  Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Shrink Boot Adapter
	Voltage - Rated	50V
Report errors?	Current Rating	22A
· ·		Report errors?

#### CA3101E20-29PF80DN Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CA3101E20-29PF80DN Payment Methods



















### CA3101E20-29PF80DN Shipping Methods













If you have any question about CA3101E20-29PF80DN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com