



CA3101E24-22PYB Information

Heisener.com

Part Number CA3101E24-22PYB
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 4POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3101E24-22PYB Specifications

| Manufacturer Part Number CA3101E24-22PYB Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation Y Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 74A | | |
|---|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationYIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating74A | Manufacturer Part Number | CA3101E24-22PYB |
| Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationYIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating74A | Manufacturer | ITT Cannon, LLC |
| Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationYIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating74A | Category | Connectors, Interconnects |
| SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationYIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating74A | | Circular Connectors |
| Connector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationYIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating74A | Package | - |
| Number of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationYIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating74A | Series | MIL-DTL-5015, CA-B |
| Shell Size - Insert Shell Size, MIL | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation Y Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 74A | Number of Positions | 4 |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationYIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating74A | Shell Size - Insert | 24-22 |
| Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation Y Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 74A | Shell Size, MIL | - |
| Fastening Type Reverse Bayonet Lock Orientation Y Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 74A | Mounting Type | Free Hanging (In-Line) |
| Orientation Y Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 74A | Termination | Solder Cup |
| Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 74A | Fastening Type | Reverse Bayonet Lock |
| Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Strain Relief 74A | Orientation | Y |
| Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 74A | Ingress Protection | IP67 - Dust Tight, Waterproof |
| Features Strain Relief Voltage - Rated 50V Current Rating 74A | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 50V Current Rating 74A | Contact Finish | Silver |
| Current Rating 74A | Features | Strain Relief |
| | Voltage - Rated | 50V |
| Report errors? | Current Rating | 74A |
| | | Report errors? |

CA3101E24-22PYB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3101E24-22PYB Payment Methods



















CA3101E24-22PYB Shipping Methods













If you have any question about CA3101E24-22PYB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com