

Heisener.com

# CA3101E28-16SBF80A176A232

## **CA3101E28-16SBF80A176A232 Information**

Part Number CA3101E28-16SBF80A176A232

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 20POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3101E28-16SBF80A176A232 Specifications

Manufacturer Part Number       CA3101E28-16SBF80A176A232         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA-B         Connector Type       Receptacle, Female Sockets         Number of Positions       20         Shell Size - Insert       28-16         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Black Zinc Cobalt Plated         Contact Finish       Gold         Features       Strain Relief         Voltage - Rated       50V         Current Rating       22A		
Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 20 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Voltage - Rated Voltage - Rated Current Rating  Connectors, Interconnects Circular Connectors MIL-OTL-5015, CA-B Receptacle, Female Sockets MIL-DTL-5015, CA-B Receptacle, Female Sockets  Alluminum (Sockets)  Contact Finish Gold Current Rating 22A	Manufacturer Part Number	CA3101E28-16SBF80A176A232
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Gold Features Strain Relief  Voltage - Rated 50V  Current Rating 22A	Number of Positions	20
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Size - Insert	28-16
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Gold  Strain Relief  22A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief  Voltage - Rated 50V  Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Gold
Current Rating 22A	Features	Strain Relief
	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

### **CA3101E28-16SBF80A176A232 Guarantees**



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3101E28-16SBF80A176A232 Payment Methods





















## CA3101E28-16SBF80A176A232 Shipping Methods













If you have any question about CA3101E28-16SBF80A176A232, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com