

CA3101E32-5S

CA3101E32-5S Information

Heisener.com	 CA3101E32-5S ITT Cannon, LLC Connectors, Interconnects Circular Connectors CONN RCPT 2POS INLINE SKT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CA3101E32-5S Specifications

Manufacturer Part NumberCA3101E32-58ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Houning TypeFree Hanging (In-Line)FarminationSolder CupOrientationN(Normal)Ingress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - RatedSVCurrent ParingSV		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesStrain ReliefVoltage - RatedStoV	Manufacturer Part Number	CA3101E32-5S
Circular ConnectorsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionH95 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesStain ReliefVoltage - Rated50V	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFee Hanging (In-Line)TerminationSolder CupFastening TypeInreadedOrientationN(Normal)Ingress Protection165 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesStain ReliefVoltage - Rated50V	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionHotson (SilverShell Material, FinishSilverFeaturesSilverFotage - RatedStrain ReliefVoltage - RatedStov		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Package	-
Number of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesStrain ReliefVoltage - Rated50V	Series	MIL-DTL-5015, CA
Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Connector Type	Receptacle, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishSilverContact FinishSilverFeaturesStrian ReliefVoltage - Rated50V	Number of Positions	2
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Shell Size - Insert	32-5
TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Termination	Solder Cup
Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Orientation	N (Normal)
Contact FinishSilverFeaturesStrain ReliefVoltage - Rated50V	Ingress Protection	IP65 - Dust Tight, Water Resistant
FeaturesStrain ReliefVoltage - Rated50V	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V	Contact Finish	Silver
	Features	Strain Relief
Current Rating 245A	Voltage - Rated	50V
	Current Rating	245A
Report error		Report errors?

CA3101E32-5S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3101E32-5S Payment Methods





If you have any question about CA3101E32-5S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com