



CA3101E32A69SB15 Information

Heisener.com

Part Number CA3101E32A69SB15 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 61POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3101E32A69SB15 Specifications

Manufacturer Part Number CA3101E32A69SB15 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 32-A69 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 8A, 22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions61Shell Size - Insert32-A69Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating8A, 22A	Manufacturer Part Number	CA3101E32A69SB15
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions61Shell Size - Insert32-A69Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating8A, 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 32-A69 Shell Size, MIL - Crimp Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated Current Rating 8A, 22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions61Shell Size - Insert32-A69Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating8A, 22A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions61Shell Size - Insert32-A69Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated50VCurrent Rating8A, 22A	Package	-
Number of Positions Shell Size - Insert 32-A69 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 8A, 22A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 8A, 22A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated 50V Current Rating 8A, 22A	Number of Positions	61
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 8A, 22A	Shell Size - Insert	32-A69
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 8A, 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 8A, 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 50V Current Rating 8A, 22A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated Current Rating 8A, 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Shielded Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Shielded Shielded 8A, 22A	Orientation	N (Normal)
Contact Finish Silver Shielded Voltage - Rated Current Rating 8A, 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shielded Voltage - Rated 50V Current Rating 8A, 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 8A, 22A	Contact Finish	Silver
Current Rating 8A, 22A	Features	Shielded
-	Voltage - Rated	50V
Report errors?	Current Rating	8A, 22A
		Report errors?

CA3101E32A69SB15 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3101E32A69SB15 Payment Methods



















CA3101E32A69SB15 Shipping Methods













If you have any question about CA3101E32A69SB15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com