



Heisener.com

## CA3102E14S-5PXB01 Information

Part Number CA3102E14S-5PXB01 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN RCPT 5POS BOX MNT PIN

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3102E14S-5PXB01 Specifications

Manufacturer Part Number     CA3102E14S-5PXB01       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     MIL-DTL-5015, CA-B       Connector Type     Receptacle, Male Pins       Number of Positions     5       Shell Size - Insert     14S-5       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Reverse Bayonet Lock       Orientation     X       Ingress Protection     IP67 - Dust Tight, Waterproof       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     50V       Current Rating     22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationXIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3102E14S-5PXB01
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationXIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 14S-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationXIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationXIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Package	-
Number of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationXIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Number of Positions	5
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationXIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Shell Size - Insert	14S-5
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Mounting Type	Panel Mount, Flange
Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 22A	Orientation	X
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

#### CA3102E14S-5PXB01 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CA3102E14S-5PXB01 Payment Methods



















## CA3102E14S-5PXB01 Shipping Methods













If you have any question about CA3102E14S-5PXB01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com