

Heisener.com

# CA3102E14S-6PBF80A176A232

## CA3102E14S-6PBF80A176A232 Information

Part Number CA3102E14S-6PBF80A176A232

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT MALE 6POS GOLD CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3102E14S-6PBF80A176A232 Specifications

Manufacturer Part Number     CA3102E14S-6PBF80A176A232       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CA-B       Connector Type     Receptacle, Male Pins       Number of Positions     6       Shell Size - Insert     14S-6       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Reverse Bayonet Lock       Orientation     N (Normal)       Ingress Protection     IP67 - Dust Tight, Waterproof       Shell Material, Finish     Aluminum Alloy, Black Zinc Cobalt Plated       Contact Finish     Gold       Features     Strain Relief       Voltage - Rated     -       Current Rating     22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated-Current Rating22A	Manufacturer Part Number	CA3102E14S-6PBF80A176A232
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated-Current Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated-Current Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated-Current Rating22A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated-Current Rating22A	Package	-
Number of Positions  Shell Size - Insert  14S-6  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  -  Current Rating  22A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  -  Current Rating  22A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Features Strain Relief  Voltage - Rated - Current Rating 22A	Number of Positions	6
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated-Current Rating22A	Shell Size - Insert	14S-6
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated - Current Rating 22A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated - Current Rating 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Gold  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated - Current Rating 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief  Voltage - Rated - Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated - Current Rating 22A	Contact Finish	Gold
Current Rating 22A	Features	Strain Relief
-	Voltage - Rated	-
Report errors?	Current Rating	22A
		Report errors?

#### CA3102E14S-6PBF80A176A232 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3102E14S-6PBF80A176A232 Payment Methods



















# CA3102E14S-6PBF80A176A232 Shipping Methods













If you have any question about CA3102E14S-6PBF80A176A232, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com