



CA3102E18-8PA206 Information

Heisener.com

Part NumberCA3102E18-8PA206ManufacturerITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 8 POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3102E18-8PA206 Specifications

Manufacturer Part NumberCA3102E18-8PA206ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A		
Category Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zine Plated, Black Contact Finish Silver Features - Voltage - Rated Connectors, Interconnects Circular Connectors Circular Connectors AMIL-DTL-5015, CA MIL-DTL-5015, CA MIL-DTL-5015, CA MIL-DTL-5015, CA MIL-DTL-5015, CA Receptacle, Male Pins 8 Solder Cup Panel Mount, Flange Panel Mount, Flange Threaded Drientation N (Normal) Ingress Protection Solder Cup Threaded Drientation D	Manufacturer Part Number	CA3102E18-8PA206
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated50V	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 18-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 50V	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated50V		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert18-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated50V	Package	-
Number of Positions Shell Size - Insert 18-8 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Features Voltage - Rated 8 8 Number of Positions 8 Aluminum Alloy, Zinc Plated, Black Silver Features - Voltage - Rated	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features Voltage - Rated 18-8 18-	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 50V	Number of Positions	8
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated50V	Shell Size - Insert	18-8
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 50V	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 50V	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 50V	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 50V	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Silver - Solver	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 50V	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V	Shell Material, Finish	Aluminum Alloy, Zinc Plated, Black
Voltage - Rated 50V	Contact Finish	Silver
	Features	-
Current Rating 22A, 41A	Voltage - Rated	50V
	Current Rating	22A, 41A
Report errors?		Report errors?

CA3102E18-8PA206 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3102E18-8PA206 Payment Methods



















CA3102E18-8PA206 Shipping Methods













If you have any question about CA3102E18-8PA206, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com