

Heisener.com

CA3102E20-29SBA34F80

CA3102E20-29SBA34F80 Information

Part Number CA3102E20-29SBA34F80

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 17 POS BOX MNT W/SKTS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3102E20-29SBA34F80 Specifications

Manufacturer Part NumberCA3102E20-29SBA34F80ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A		
Category Circular Connectors Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features - Voltage - Rated Connectors, Interconnects Circular Connectors MIL-DTL-5015, CA-B MIL-DTL-5015, CA-B Receptacle, Female Sockets NIL-DTL-5015, CA-B Receptacle, Female Sockets NECTOR BROWNES Receptacle, Female Sockets 17 Normal Shell Mounting Type Panel Mount, Flange Panel Moun	Manufacturer Part Number	CA3102E20-29SBA34F80
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features - Voltage - Rated Circular Connectors MIL-DTL-5015, CA-B	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Crimp Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 50V		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 50V	Package	-
Number of Positions Shell Size - Insert 20-29 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 17 20-29 Panel Mount, Flange Panel Mount, Flange Crimp Auminum Flange Silver - Voltage - Rated	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features Voltage - Rated 20-29 Annual Lock Auminum Alloy, Nickel Plated 50V	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 50V	Number of Positions	17
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated50V	Shell Size - Insert	20-29
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 50V	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 50V	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 50V	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 50V	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Shell Material, Finish Silver - 50V	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 50V	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated 50V	Contact Finish	Silver
	Features	-
Current Rating 22A	Voltage - Rated	50V
	Current Rating	22A
Report errors?		Report errors?

CA3102E20-29SBA34F80 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3102E20-29SBA34F80 Payment Methods



















CA3102E20-29SBA34F80 Shipping Methods













If you have any question about CA3102E20-29SBA34F80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com