



CA3102E28-10SBF80 Information

Heisener.com

Part Number CA3102E28-10SBF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 7 POS BOX MNT W/SKTS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3102E28-10SBF80 Specifications

Manufacturer Part NumberCA3102E28-10SBF80ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 74A, 135A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 74A, 135A	Manufacturer Part Number	CA3102E28-10SBF80
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 74A, 135A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 74A, 135A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 74A, 135A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 74A, 135A	Package	-
Number of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 74A, 135A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 74A, 135A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 41A, 74A, 135A	Number of Positions	7
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 74A, 135A	Shell Size - Insert	28-10
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 74A, 135A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 74A, 135A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 74A, 135A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 74A, 135A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 41A, 74A, 135A	Orientation	N (Normal)
Contact Finish Features Voltage - Rated Current Rating Silver - 41A, 74A, 135A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 41A, 74A, 135A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 41A, 74A, 135A	Contact Finish	Silver
Current Rating 41A, 74A, 135A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	41A, 74A, 135A
		Report errors?

CA3102E28-10SBF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3102E28-10SBF80 Payment Methods



















CA3102E28-10SBF80 Shipping Methods













If you have any question about CA3102E28-10SBF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com