

Heisener.com

# CA3102E28-11PWB109

### CA3102E28-11PWB109 Information

Part Number CA3102E28-11PWB109

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 22 POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CA3102E28-11PWB109 Specifications

| Manufacturer Part NumberCA3102E28-11PWB109ManufacturerITT Cannon, LLCCategoryConnectors, Interconnects<br>Circular ConnectorsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions22Shell Size - Insert28-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationWIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A |                          |   |
|--|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions22Shell Size - Insert28-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationWIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A   | Manufacturer Part Number | CA3102E28-11PWB109                        |
| Package-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions22Shell Size - Insert28-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationWIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A  | Manufacturer             | ITT Cannon, LLC                           |
| Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Male Pins Number of Positions 22 Shell Size - Insert 28-11 Shell Size, MIL - Contact Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Sive - Rated Current Rating 22A, 41A  | Category                 | Connectors, Interconnects                 |
| SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Male PinsNumber of Positions22Shell Size - Insert28-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationWIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A  |                          | Circular Connectors                       |
| Connector TypeReceptacle, Male PinsNumber of Positions22Shell Size - Insert28-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationWIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A  | Package                  | -   |
| Number of Positions  Shell Size - Insert  28-11  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Reverse Bayonet Lock  Orientation  Ingress Protection  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  50V  Current Rating  22A, 41A   | Series                   | MIL-DTL-5015, CA-B                        |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation W Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A   | Connector Type           | Receptacle, Male Pins                     |
| Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Reverse Bayonet Lock Orientation W Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A, 41A  | Number of Positions      | 22  |
| Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Reverse Bayonet Lock  Orientation W  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 50V  Current Rating 22A, 41A  | Shell Size - Insert      | 28-11                                     |
| Termination Crimp Fastening Type Reverse Bayonet Lock Orientation W Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A   | Shell Size, MIL          | -   |
| Fastening Type Reverse Bayonet Lock Orientation W Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A   | Mounting Type            | Panel Mount, Flange                       |
| Orientation W Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A   | Termination              | Crimp                                     |
| Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 22A, 41A   | Fastening Type           | Reverse Bayonet Lock                      |
| Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 22A, 41A   | Orientation              | W   |
| Contact Finish  Features  Voltage - Rated  Current Rating  Silver  - 22A, 41A  | Ingress Protection       | IP67 - Dust Tight, Waterproof             |
| Features - Voltage - Rated 50V Current Rating 22A, 41A   | Shell Material, Finish   | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 50V<br>Current Rating 22A, 41A   | Contact Finish           | Silver                                    |
| Current Rating 22A, 41A  | Features                 | -   |
|  | Voltage - Rated          | 50V                                       |
| Report errors?   | Current Rating           | 22A, 41A                                  |
|  |                          | Report errors?                            |

#### CA3102E28-11PWB109 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CA3102E28-11PWB109 Payment Methods



















## CA3102E28-11PWB109 Shipping Methods













If you have any question about CA3102E28-11PWB109, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com