



CA3102E32-1SB01 Information

Heisener.com

Part Number CA3102E32-1SB01 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 5 POS BOX MNT W/SKTS

Secription Converge 1 3 1 05 Box White

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3102E32-1SB01 Specifications

Manufacturer Part Number CA3102E32-1SB01 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 32-1 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert32-1Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 245A	Manufacturer Part Number	CA3102E32-1SB01
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 32-1 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 41A, 245A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 32-1 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 41A, 245A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 32-1 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert32-1Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 245A	Package	-
Number of Positions Shell Size - Insert 32-1 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Current Rating 41A, 245A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Number of Positions	5
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A, 245A	Shell Size - Insert	32-1
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A, 245A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 41A, 245A	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating 41A, 245A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 41A, 245A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 41A, 245A	Contact Finish	Silver
Current Rating 41A, 245A	Features	-
	Voltage - Rated	50V
Report errors?	Current Rating	41A, 245A
		Report errors?

CA3102E32-1SB01 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3102E32-1SB01 Payment Methods



















CA3102E32-1SB01 Shipping Methods













If you have any question about CA3102E32-1SB01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com