



CA3102E32-5SXB Information

Heisener.com

Part Number CA3102E32-5SXB **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 2 POS BOX MNT W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3102E32-5SXB Specifications

Manufacturer Part Number CA3102E32-5SXB Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 245A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating Connectors, Interconnects Circular Connectors HIL-DTL-5015, CA-B Receptacle, Female Sockets Allu-DTL-5015, CA-B Receptacle, Female Sockets - Voltage - Rated Sov Current Rating Connectors MIL-DTL-5015, CA-B Receptacle Pemale Sockets - Voltage - Rated Sov Current Rating	Manufacturer Part Number	CA3102E32-5SXB
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 2 45A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 245A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 245A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationXIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating245A	Package	-
Number of Positions Shell Size - Insert 32-5 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 50V Current Rating 22- 32-5 32-5 Aluminum, Flange Panel Mount, Flange Reverse Bayonet Lock Aluminum Alloy Aluminum Alloy Silver Features - Voltage - Rated 50V 245A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 245A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 245A	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationXIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating245A	Shell Size - Insert	32-5
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 245A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 245A	Mounting Type	Panel Mount, Flange
Orientation X Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 245A	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating IP67 - Dust Tight, Waterproof Aluminum Alloy, Olive Drab Cadmium Plated Silver - 245A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 245A	Orientation	X
Contact Finish Silver Features - Voltage - Rated Current Rating 245A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 245A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 245A	Contact Finish	Silver
Current Rating 245A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	245A
		Report errors?

CA3102E32-5SXB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3102E32-5SXB Payment Methods



















CA3102E32-5SXB Shipping Methods













If you have any question about CA3102E32-5SXB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com