



CA3102R12S-3SF80 Information

Heisener.com

Part Number CA3102R12S-3SF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 2 POS BOX MNT W/SKTS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3102R12S-3SF80 Specifications

Manufacturer Part Number CA3102R12S-3SF80 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3102R12S-3SF80
Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Package	-
Number of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 12S-3 12S	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Shell Size - Insert	12S-3
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Silver - 22A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 22A	Orientation	N (Normal)
Contact Finish Features Voltage - Rated Current Rating Silver - 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3102R12S-3SF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3102R12S-3SF80 Payment Methods



















CA3102R12S-3SF80 Shipping Methods













If you have any question about CA3102R12S-3SF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com