



CA3102R28-9PYF80 Information

Heisener.com

Part Number CA3102R28-9PYF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 12 POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3102R28-9PYF80 Specifications

Manufacturer Part Number CA3102R28-9PYF80 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 28-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert28-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Manufacturer Part Number	CA3102R28-9PYF80
Package-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert28-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 28-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 22A, 41A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert28-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert28-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Package	-
Number of Positions12Shell Size - Insert28-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Series	MIL-DTL-5015, CA
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Number of Positions	12
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Shell Size - Insert	28-9
Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Threaded Orientation Y Ingress Protection Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating Threaded Threaded Y Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Silver - Voltage - Rated 50V Current Rating	Mounting Type	Panel Mount, Flange
Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Termination	Crimp
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Silver - 22A, 41A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 22A, 41A	Orientation	Y
Contact Finish Features Voltage - Rated Current Rating Silver - 22A, 41A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	22A, 41A
		Report errors?

CA3102R28-9PYF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3102R28-9PYF80 Payment Methods



















CA3102R28-9PYF80 Shipping Methods













If you have any question about CA3102R28-9PYF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com