

CA3106E14S-2PF80A206

CA3106E14S-2PF80A206 Information

Heisener.com	 CA3106E14S-2PF80A206 ITT Cannon, LLC Connectors, Interconnects Circular Connectors CONN PLUG 4POS INLINE W/PINS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Juote

CA3106E14S-2PF80A206 Specifications

Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Category Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 14S-2 Mounting Type Free Hanging (In-Line) Free Hanging (In-Line) Crimp Fastening Type N(Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Silver Contact Finish Silver Features Silver Voltage - Rated Strain Relief		
CategoryConnectors, Interconnects Circular ConnectorsPackage-PackageMIL-DTL-5015, CASeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN(Normal)Ingress ProtectionN(Normal)Shell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishStrim ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3106E14S-2PF80A206
Circular ConnectorsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionSilverShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeCrimpFastening TypeN(Normal)DrientationP65 - Dust Tight, Water ResistantShell Material, FinishSilverContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishSilverContact FinishSilverFeaturesStrain ReliefVoltage - Rated22A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishSilverFeaturesStain ReliefVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions4Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage - Rated22A	Series	MIL-DTL-5015, CA
Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated22A	Connector Type	Plug, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Number of Positions	4
Mounting TypeFree Hanging (In-Line)FerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Size - Insert	14S-2
TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Termination	Crimp
Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Orientation	N (Normal)
Contact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
FeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Material, Finish	Aluminum Alloy, Zinc Plated, Black
Voltage - Rated50VCurrent Rating22A	Contact Finish	Silver
Current Rating 22A	Features	Strain Relief
-	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3106E14S-2PF80A206 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about CA3106E14S-2PF80A206, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com