

Heisener.com

# CA3106E14S-5SBF80A176A232

## CA3106E14S-5SBF80A176A232 Information

Part Number CA3106E14S-5SBF80A176A232

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 5POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3106E14S-5SBF80A176A232 Specifications

| Manufacturer Part Number     CA3106E14S-SSBF80A176A232       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CA-B       Connector Type     Plug, Female Sockets       Number of Positions     5       Shell Size - Insert     14S-5       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Reverse Bayonet Lock       Orientation     N (Normal)       Ingress Protection     IP67 - Dust Tight, Waterproof       Shell Material, Finish     Aluminum Alloy, Black Zinc Cobalt Plated       Contact Finish     Gold       Features     Strain Relief       Voltage - Rated     50V       Current Rating     22A |                          |  |
|---|--------------------------|--|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A  | Manufacturer Part Number | CA3106E14S-5SBF80A176A232                |
| Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Manufacturer             | ITT Cannon, LLC                          |
| Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Category                 | Connectors, Interconnects                |
| SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   |                          | Circular Connectors                      |
| Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Package                  | -  |
| Number of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Series                   | MIL-DTL-5015, CA-B                       |
| Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief  Voltage - Rated Current Rating 22A  | Connector Type           | Plug, Female Sockets                     |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Features Strain Relief  Voltage - Rated 50V  Current Rating 22A   | Number of Positions      | 5  |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A   | Shell Size - Insert      | 14S-5                                    |
| Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A   | Shell Size, MIL          | -  |
| Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A   | Mounting Type            | Free Hanging (In-Line)                   |
| Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A   | Termination              | Crimp                                    |
| Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A  | Fastening Type           | Reverse Bayonet Lock                     |
| Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Gold  Strain Relief  22A  | Orientation              | N (Normal)                               |
| Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A   | Ingress Protection       | IP67 - Dust Tight, Waterproof            |
| Features Strain Relief  Voltage - Rated 50V  Current Rating 22A   | Shell Material, Finish   | Aluminum Alloy, Black Zinc Cobalt Plated |
| Voltage - Rated 50V<br>Current Rating 22A   | Contact Finish           | Gold                                     |
| Current Rating 22A  | Features                 | Strain Relief                            |
| č   | Voltage - Rated          | 50V                                      |
| Report errors?  | Current Rating           | 22A                                      |
|   |                          | Report errors?                           |

#### CA3106E14S-5SBF80A176A232 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3106E14S-5SBF80A176A232 Payment Methods





















### CA3106E14S-5SBF80A176A232 Shipping Methods













If you have any question about CA3106E14S-5SBF80A176A232, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com