

Heisener.com

CA3106E14S-6PF80F187

CA3106E14S-6PF80F187 Information

Part Number CA3106E14S-6PF80F187

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 6POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106E14S-6PF80F187 Specifications

Manufacturer Part Number CA3106E14S-6PF80F187 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3106E14S-6PF80F187
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA
Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 50V Current Rating 22A	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Size - Insert	14S-6
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Strain Relief 22A	Orientation	N (Normal)
Contact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Strain Relief
	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3106E14S-6PF80F187 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106E14S-6PF80F187 Payment Methods



















CA3106E14S-6PF80F187 Shipping Methods













If you have any question about CA3106E14S-6PF80F187, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com