



Heisener.com

CA3106E16-9SBA34-01 Information

Part Number CA3106E16-9SBA34-01

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 4POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106E16-9SBA34-01 Specifications

| Manufacturer Part NumberCA3106E16-9SBA34-01ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert16-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41AReport errors? | | |
|--|--------------------------|-------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert16-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A | Manufacturer Part Number | CA3106E16-9SBA34-01 |
| Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert16-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A | Manufacturer | ITT Cannon, LLC |
| Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert16-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A | Category | Connectors, Interconnects |
| SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert16-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A | | Circular Connectors |
| Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert16-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A | Package | - |
| Number of Positions Shell Size - Insert 16-9 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating 22A, 41A | Series | MIL-DTL-5015, CA-B |
| Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating 16-9 Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Aluminum (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Aluminum (In-Line) Silver Footomet Finish Silver Features Strain Relief 22A, 41A | Connector Type | Plug, Female Sockets |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A | Number of Positions | 4 |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A | Shell Size - Insert | 16-9 |
| Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A | Shell Size, MIL | - |
| Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A | Mounting Type | Free Hanging (In-Line) |
| Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A | Termination | Crimp |
| Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A | Fastening Type | Reverse Bayonet Lock |
| Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A, 41A | Orientation | N (Normal) |
| Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A, 41A | Ingress Protection | IP67 - Dust Tight, Waterproof |
| Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A | Shell Material, Finish | Aluminum Alloy, Nickel Plated |
| Voltage - Rated 50V Current Rating 22A, 41A | Contact Finish | Silver |
| Current Rating 22A, 41A | Features | Strain Relief |
| | Voltage - Rated | 50V |
| Report errors? | Current Rating | 22A, 41A |
| | | Report errors? |

CA3106E16-9SBA34-01 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106E16-9SBA34-01 Payment Methods




































If you have any question about CA3106E16-9SBA34-01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com