

Heisener.com

CA3106E18-1PBA34F80

CA3106E18-1PBA34F80 Information

Part Number CA3106E18-1PBA34F80

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 10POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106E18-1PBA34F80 Specifications

Manufacturer Part NumberCA3106E18-1PBA34F80ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent RatingEeport errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3106E18-1PBA34F80
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 10 Shell Size - Insert 18-1 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating Circular Connectors MIL-DTL-5015, CA-B Plug, Male Pins No. Nomal 10 Crimp Free Hanging (In-Line) Crimp Fastering Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated SoV Current Rating	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions Shell Size - Insert 18-1 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating 10 18-1 1	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Number of Positions	10
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Size - Insert	18-1
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Strain Relief
-	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3106E18-1PBA34F80 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106E18-1PBA34F80 Payment Methods



















CA3106E18-1PBA34F80 Shipping Methods













If you have any question about CA3106E18-1PBA34F80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com