



CA3106E18-1SA34 Information

Heisener.com

Part Number CA3106E18-1SA34 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 10POS INLINE W/SKTS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106E18-1SA34 Specifications

Manufacturer Part Number CA3106E18-ISA34 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 10 Shell Size - Insert 18-1 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3106E18-1SA34
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Package	-
Number of Positions10Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA
Shell Size - Insert18-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Number of Positions	10
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A	Shell Size - Insert	18-1
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Threaded N (Normal) IP65 - Dust Tight, Water Resistant Strain Relief Aluminum Alloy, Nickel Plated Silver Strain Relief	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Z2A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Strain Relief Voltage - Rated Current Rating 22A	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Strain Relief
	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

CA3106E18-1SA34 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106E18-1SA34 Payment Methods



















CA3106E18-1SA34 Shipping Methods













If you have any question about CA3106E18-1SA34, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com