



### CA3106E20-22PW Information

Heisener.com

**Part Number** CA3106E20-22PW **Manufacturer** ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 6POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CA3106E20-22PW Specifications

Manufacturer Part NumberCA3106E20-22PWManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 74AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 74A	Manufacturer Part Number	CA3106E20-22PW
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 74A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 74A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 74A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 74A	Package	-
Number of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 74A	Series	MIL-DTL-5015, CA
Shell Size - Insert 20-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 74A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 50V Current Rating 22A, 74A	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 74A	Shell Size - Insert	20-22
Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 74A	Shell Size, MIL	-
Fastening Type Threaded Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 74A	Mounting Type	Free Hanging (In-Line)
Orientation W Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 22A, 74A	Termination	Solder Cup
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 22A, 74A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Strain Relief  22A, 74A	Orientation	W
Contact Finish Silver  Features Strain Relief Voltage - Rated Current Rating 22A, 74A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features Strain Relief  Voltage - Rated 50V  Current Rating 22A, 74A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 74A	Contact Finish	Silver
Current Rating 22A, 74A	Features	Strain Relief
-	Voltage - Rated	50V
Report errors?	Current Rating	22A, 74A
		Report errors?

### CA3106E20-22PW Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CA3106E20-22PW Payment Methods

































If you have any question about CA3106E20-22PW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com