



## CA3106E20-4SA34 Information

Heisener.com

**Part Number** CA3106E20-4SA34 **Manufacturer** ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 4POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3106E20-4SA34 Specifications

| Manufacturer Part Number  Manufacturer  ITT Cannon, LLC  Category  Connectors, Interconnects  Circular Connectors  Package  - Series  MIL-DTL-5015, CA  Connector Type  Plug, Female Sockets  Number of Positions  4  Shell Size - Insert  20-4  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Ingress Protection  Ingress Protection  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  41A  Connectors  Connectors  Connectors  Circular Connectors  AllL-DTL-5015, CA  AllL-DTL-5015, CA  Connector Type  Plug, Female Sockets  AllL-DTL-5015, CA  Connector Type  Plug, Female Sockets  All AllA  Report errors?   |                          |                                    |
|--|--------------------------|------------------------------------|
| Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 20-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Nipes Protection Ipes - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating  - Connectors, Interconnects Circular Connectors  MIL-DTL-5015, CA  MIL-DTL-5015, CA  MIL-DTL-5015, CA  10  NIL-DTL-5015, CA  10  Number of Position Number o | Manufacturer Part Number | CA3106E20-4SA34                    |
| Circular Connectors  Package - Series  MIL-DTL-5015, CA  Connector Type Plug, Female Sockets  Number of Positions 4  Shell Size - Insert 20-4  Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Threaded Orientation N (Normal)  Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated  Contact Finish Features Strain Relief Voltage - Rated 50V  Current Rating  MIL-DTL-5015, CA  Aluminum Alloy, Nickel Plated  Contact Finish Silver  Features  Strain Relief  Voltage - Rated 50V  | Manufacturer             | ITT Cannon, LLC                    |
| Package - Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 20-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A   | Category                 | Connectors, Interconnects          |
| Series MIL-DTL-5015, CA Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 20-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A   |                          | Circular Connectors                |
| Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert20-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated50VCurrent Rating41A  | Package                  | -                                  |
| Number of Positions  Shell Size - Insert  20-4  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Nickel Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  41A   | Series                   | MIL-DTL-5015, CA                   |
| Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Nickel Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  41A  | Connector Type           | Plug, Female Sockets               |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated  Contact Finish Silver Features Strain Relief  Voltage - Rated 50V  Current Rating 41A  | Number of Positions      | 4                                  |
| Mounting Type Free Hanging (In-Line)  Termination Solder Cup Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A  | Shell Size - Insert      | 20-4                               |
| Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A   | Shell Size, MIL          | -                                  |
| Fastening Type  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Nickel Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  41A  | Mounting Type            | Free Hanging (In-Line)             |
| Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 50V Current Rating 41A  | Termination              | Solder Cup                         |
| Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Nickel Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  41A   | Fastening Type           | Threaded                           |
| Shell Material, Finish Contact Finish Silver Strain Relief Voltage - Rated Current Rating 41A  | Orientation              | N (Normal)                         |
| Contact Finish Silver Strain Relief Voltage - Rated Current Rating 41A   | Ingress Protection       | IP65 - Dust Tight, Water Resistant |
| Features Strain Relief  Voltage - Rated 50V  Current Rating 41A  | Shell Material, Finish   | Aluminum Alloy, Nickel Plated      |
| Voltage - Rated 50V Current Rating 41A   | Contact Finish           | Silver                             |
| Current Rating 41A   | Features                 | Strain Relief                      |
| -  | Voltage - Rated          | 50V                                |
| Report errors?   | Current Rating           | 41A                                |
|  |                          | Report errors?                     |

### CA3106E20-4SA34 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CA3106E20-4SA34 Payment Methods





















## CA3106E20-4SA34 Shipping Methods













If you have any question about CA3106E20-4SA34, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com