



CA3106E24-9SB13 Information

Heisener.com

Part Number CA3106E24-9SB13 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 2POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106E24-9SB13 Specifications

Manufacturer Part NumberCA3106E24-9SB13ManufacturerITT Cannon, LLCCategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert24-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated50VCurrent Rating135A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert24-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated50VCurrent Rating135A	Manufacturer Part Number	CA3106E24-9SB13
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 24-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded, Strain Relief Voltage - Rated Current Rating 135A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 24-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated Current Rating 135A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 24-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 50V Current Rating 135A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert24-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated50VCurrent Rating135A	Package	-
Number of Positions Shell Size - Insert 24-9 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded, Strain Relief Voltage - Rated 50V Current Rating 135A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 50V Current Rating 135A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 50V Current Rating 135A	Number of Positions	2
Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 50V Current Rating 135A	Shell Size - Insert	24-9
Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 50V Current Rating 135A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated Current Rating 135A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 50V Current Rating 135A	Termination	Solder
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated Current Rating 135A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Shielded, Strain Relief 135A	Orientation	N (Normal)
Contact Finish Silver Shielded, Strain Relief Voltage - Rated Current Rating 135A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shielded, Strain Relief Voltage - Rated 50V Current Rating 135A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 135A	Contact Finish	Silver
Current Rating 135A	Features	Shielded, Strain Relief
-	Voltage - Rated	50V
Report errors?	Current Rating	135A
		Report errors?

CA3106E24-9SB13 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106E24-9SB13 Payment Methods



















CA3106E24-9SB13 Shipping Methods













If you have any question about CA3106E24-9SB13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com