



Heisener.com

CA3106E28-20SBA176 Information

Part Number CA3106E28-20SBA176

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 14POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106E28-20SBA176 Specifications

Manufacturer Part Number CA3106E28-20SBA176 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 14 Shell Size - Insert 28-20 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A	Manufacturer Part Number	CA3106E28-20SBA176
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 14 Shell Size - Insert 28-20 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating 2-Canact Finish Circular Connectors MIL-DTL-5015, CA-B MIL	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 14 Shell Size - Insert 28-20 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A, 41A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated50VCurrent Rating22A, 41A	Package	-
Number of Positions Shell Size - Insert 28-20 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Number of Positions	14
Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Shell Size - Insert	28-20
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 22A, 41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Gold Strain Relief 22A, 41A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief Voltage - Rated 50V Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 41A	Contact Finish	Gold
Current Rating 22A, 41A	Features	Strain Relief
	Voltage - Rated	50V
Report errors?	Current Rating	22A, 41A
		Report errors?

CA3106E28-20SBA176 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106E28-20SBA176 Payment Methods



















CA3106E28-20SBA176 Shipping Methods













If you have any question about CA3106E28-20SBA176, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com