



CA3106F16-10SB02 Information

Heisener.com

Part Number CA3106F16-10SB02 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 3POS INLINE W/SKTS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106F16-10SB02 Specifications

Manufacturer Part Number CA3106F16-10SB02 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating41A	Manufacturer Part Number	CA3106F16-10SB02
Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating41A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating41A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating41A	Package	-
Number of Positions Shell Size - Insert 16-10 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shrink Boot Adapter Voltage - Rated Current Rating 41A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated Current Rating 41A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A	Number of Positions	3
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A	Shell Size - Insert	16-10
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Shrink Boot Adapter 41A	Orientation	N (Normal)
Contact Finish Silver Shrink Boot Adapter Voltage - Rated Current Rating 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 41A	Contact Finish	Silver
Current Rating 41A	Features	Shrink Boot Adapter
č	Voltage - Rated	50V
Report errors?	Current Rating	41A
		Report errors?

CA3106F16-10SB02 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106F16-10SB02 Payment Methods





















CA3106F16-10SB02 Shipping Methods













If you have any question about CA3106F16-10SB02, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com