



## CA3106F20-7PXF80 Information

Heisener.com

Part Number CA3106F20-7PXF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 8POS INLINE W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### CA3106F20-7PXF80 Specifications

Manufacturer Part Number       CA3106F20-7PXF80         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA         Connector Type       Plug, Male Pins         Number of Positions       8         Shell Size - Insert       20-7         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Threaded         Orientation       X         Ingress Protection       IP65 - Dust Tight, Water Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       50V         Current Rating       22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions8Shell Size - Insert20-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Manufacturer Part Number	CA3106F20-7PXF80
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions8Shell Size - Insert20-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions8Shell Size - Insert20-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions8Shell Size - Insert20-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions8Shell Size - Insert20-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Package	-
Number of Positions8Shell Size - Insert20-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Series	MIL-DTL-5015, CA
Shell Size - Insert20-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A	Number of Positions	8
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationXIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A	Shell Size - Insert	20-7
Termination Crimp Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Shell Size, MIL	-
Fastening Type Threaded Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation X Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Termination	Crimp
Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated - Silver - 22A	Orientation	X
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 50V Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
	Voltage - Rated	50V
Report errors?	Current Rating	22A
		Report errors?

### CA3106F20-7PXF80 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3106F20-7PXF80 Payment Methods



















# CA3106F20-7PXF80 Shipping Methods













If you have any question about CA3106F20-7PXF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com