



CA3106F22-28PB Information

Heisener.com

Part Number CA3106F22-28PB **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 7POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106F22-28PB Specifications

Manufacturer Part Number CA3106F22-28PB Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 22-28 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Manufacturer Part Number	CA3106F22-28PB
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 22-28 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating 41A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Package	-
Number of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Number of Positions	7
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating41A	Shell Size - Insert	22-28
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 41A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 41A	Orientation	N (Normal)
Contact Finish Features Voltage - Rated Current Rating Silver - 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 41A	Contact Finish	Silver
Current Rating 41A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	41A
		Report errors?

CA3106F22-28PB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106F22-28PB Payment Methods



















CA3106F22-28PB Shipping Methods













If you have any question about CA3106F22-28PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com