



### CA3106F24-22PYF80 Information

Heisener.com

Part Number CA3106F24-22PYF80
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN PLUG 4POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CA3106F24-22PYF80 Specifications

| Manufacturer Part Number  Manufacturer  ITT Cannon, LLC  Category  Connectors, Interconnects  Circular Connectors  Package  Series  MIL-DTL-5015, CA  Connector Type  Plug, Male Pins  Number of Positions  4  Shell Size - Insert  24-22  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Threaded  Orientation  Y  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  50V  Page 1 agree 1 agree 2 |                          |   |
|---|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A  | Manufacturer Part Number | CA3106F24-22PYF80                         |
| Circular Connectors  Package - Series MIL-DTL-5015, CA Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating 74A   | Manufacturer             | ITT Cannon, LLC                           |
| Package-SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A   | Category                 | Connectors, Interconnects                 |
| SeriesMIL-DTL-5015, CAConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A   |                          | Circular Connectors                       |
| Connector TypePlug, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A   | Package                  | -   |
| Number of Positions  Shell Size - Insert  24-22  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Crimp  Fastening Type  Threaded  Orientation  Y  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  Current Rating  74A   | Series                   | MIL-DTL-5015, CA                          |
| Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A   | Connector Type           | Plug, Male Pins                           |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A   | Number of Positions      | 4   |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationYIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating74A  | Shell Size - Insert      | 24-22                                     |
| Termination Crimp Fastening Type Threaded Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A  | Shell Size, MIL          | -   |
| Fastening Type  Threaded  Orientation  Y  Ingress Protection  Shell Material, Finish  Contact Finish  Features  Voltage - Rated  Current Rating  Threaded  Threaded  Y  Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  Voltage - Rated  74A  | Mounting Type            | Free Hanging (In-Line)                    |
| Orientation Y Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 74A  | Termination              | Crimp                                     |
| Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  4  74A  | Fastening Type           | Threaded                                  |
| Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  Voltage - Rated  74A   | Orientation              | Y   |
| Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  74A   | Ingress Protection       | IP65 - Dust Tight, Water Resistant        |
| Features - Voltage - Rated 50V Current Rating 74A   | Shell Material, Finish   | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 50V<br>Current Rating 74A   | Contact Finish           | Silver                                    |
| Current Rating 74A  | Features                 | -   |
|   | Voltage - Rated          | 50V                                       |
| Panant among?   | Current Rating           | 74A                                       |
| Report errors?  |                          | Report errors?                            |

#### CA3106F24-22PYF80 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3106F24-22PYF80 Payment Methods



















## CA3106F24-22PYF80 Shipping Methods













If you have any question about CA3106F24-22PYF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com