



CA3106F28-9SB01 Information

Heisener.com

Part Number CA3106F28-9SB01 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 12POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3106F28-9SB01 Specifications

Manufacturer Part Number CA3106F28-9SB01 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Female SocketsNumber of Positions12Shell Size - Insert28-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Manufacturer Part Number	CA3106F28-9SB01
Circular Connectors Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-9 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Current Rating 2Canact Finish Circular Connectors MIL-DTL-5015, CA-B MIL-D	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-9 Shell Size, MIL - Crimp Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 222A, 41A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions12Shell Size - Insert28-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Package	-
Number of Positions Shell Size - Insert 28-9 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Current Rating 12 28-9 Free Hanging (In-Line) Crimp Free Hanging (In-Line) Aluminum Contact Silver Features - Voltage - Rated 50V 22A, 41A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Rastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Number of Positions	12
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A, 41A	Shell Size - Insert	28-9
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A, 41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver	Orientation	N (Normal)
Contact Finish Features Voltage - Rated Current Rating Silver - 22A, 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 50V Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	-
-	Voltage - Rated	50V
Report errors?	Current Rating	22A, 41A
		Report errors?

CA3106F28-9SB01 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3106F28-9SB01 Payment Methods



















CA3106F28-9SB01 Shipping Methods













If you have any question about CA3106F28-9SB01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com